



MATERIAL SAFETY DATA SHEET

for Fabric-Wrapped Fiberglass Panel Product

1. PRODUCT IDENTIFICATION

TRADE NAME: (AS LABELED)	ABSORBOR™ PANEL ABSORBOR™ HI-IMPACT PANEL BAD™ PANEL BROADSORBER
MANUFACTURER'S NAME:	RPG ACOUSTICAL SYSTEMS, LLC.
ADDRESS:	99 SOUTH ST. PASSAIC, NJ 07055
PHONE NUMBER:	(973)-916-1166
DATE PREPARED OR REVISED:	APRIL 18, 2022

2. HAZARDOUS INGREDIENTS

CHEMICAL NAMES	CAS #	PERCENT	AGENCY	EXPOSURE LIMITS
FIBROUS GLASS	65997-17-3	< 50% by weight	OSHA	PEL 5.0 mg/m ³
			ACGIH	TLV 10.0 mg/m ³
CYCLOHEXANE	110-82-7	Negligible	OSHA + ACGIH	TWA 300 ppm
N-HEXANE	110-54-3	Negligible	OSHA + ACGIH	TWA 50 ppm
ACETALDEHYDE	75-07-0	Negligible		

* Based on sensory exposure

3. HAZARD IDENTIFICATION

Overview: Manual or mechanical cutting processes performed on the panel can result in generation of glass fiber dust.

Primary Health Hazards: Glass fiber dust.

Primary Route(s) of Exposure:

Ingestion: Not applicable.

Skin: Wash affected areas with soap and rinse with large amounts of water. Get medical attention if rash or irritation persists or dermatitis occurs.

Inhalation: Fiber dust may cause unpleasant obstruction in the nasal passages, resulting in dryness of nose, dry cough, sneezing and headaches. Remove to fresh



air. Get medical attention if irritation persists, severe coughing or breathing difficulty occurs.

Eye: Fiber dust may cause mechanical irritation. Treat dust in eye as foreign object. Flush eyes with large amounts of water. Remove to fresh air. If irritation persists, seek medical attention.

Medical Conditions Generally Aggravated by Exposure: Fiber dust may aggravate pre-existing respiratory conditions or allergies.

Disposal: Dispose of panels in accordance with federal, state and local regulations. The primary method of disposal is in an industrial landfill.