



FILE REQUIREMENTS

Customer to provide a Vector based file format that is at least 300 DPI at full size to RPG.

Note: See the Perfecto® Micro data sheet for acoustic information.

PRODUCT OVERVIEW

The **Perfecto® Micro FX Panel** combines durable, architectural-grade wall or ceiling panel solutions with crisp, high-resolution graphics and excellent sound-absorbing qualities. Provide custom image files or work with your RPG Sales Representative to select the right image to enhance your project. Utilizing hundreds of thousands of nominal 0.4mm **laser micro-perforations** and available in a high recycled content, ULEF, Class A fire-rated and FSC®-certified MDF core with an optional black fleece backer, the **Perfecto® Micro FX Panel** can achieve up to an average **NRC=0.90** while maintaining the ambiance of the space with reflections at the highest frequencies.

SIZING

- Standard Panel: 4' W x 8' L x 3/4" T
- Maximum Panel: up to 5' W x 12' L may be available (Custom panel widths and lengths are available)
- Perforations: Nominal 0.4mm dia. holes on 2mm staggered centers
- Wood panels weigh approx. 1.50 lbs/ft²

CORE FIRE RATING

Class A (per ASTM E-84)

FINISH

The **Perfecto® Micro FX Panel** is available in custom-printed multi-colored graphics provided by the Architect or Interior Designer. The graphic can be single or multiple panels. Get in touch with your RPG Sales Representative to discuss your unique project and let your imagination run wild!

INSTALLATION

Mounting options for the **Perfecto® FX Panel** include wall systems (Z-clips, direct screw attached), either surface-mounted or with a variety of cavity depths starting at 1-3/4" total system depth, or ceiling systems (Torsion Springs for downward access, RPG C-clips for lift and shift access, direct screw attached) with options for standard 15/16" HD T-grid supplied by others.